

LIGHTING AND GRIP BATTERIES

Long lasting and powerful batteries for all types of lighting and grip equipment, from remote heads to 800W DC ballasts.



BATTERY	MEGA 30	MEGA-LITE 30	MEGA-LITE 20	POWERBANK	POWERBELT
AMP HOUR	30V 30Ah	30V 30Ah or 12V 75Ah	30V 20Ah or 12V 50Ah	30V 15Ah	30V 15Ah
WATT HOUR	900Wh	900Wh	600Wh	450Wh	450Wh
400W LOAD RUNTIME	2Hrs	2Hrs	1.25Hrs	1Hr	1Hr
CHARGER	Mega	Mega	Mega	Super Silver	Super Silver
OUTPUT VOLTAGES & SOCKETS	30V Three standard output + one switchable high current output	30V or 12V Switchable. Four standard output + one high current output	30V or 12V Switchable. Four standard output + one high current output	30V One standard output + one high current output	30V Two standard output + one high current output
SIZE	H 300mm/ 11.8" L 310mm/ 12.2" W 150mm/ 5.9"	H 292mm/ 11.5" L 307mm/ 12.1" W 143mm/ 5.6"	H 292mm/ 11.5" L 220mm/ 8.7" W 143mm/ 5.6"	H 250mm/ 9.8" L 245mm/ 9.6" W 120mm/ 4.7"	H 127mm/ 5" L 740mm/ 29" W 50mm/ 2"
WEIGHT	17.5Kg / 38.5 lbs	18Kg / 39.6 lbs	13Kg / 28.6 lbs	7.5 Kg / 16.5 lbs	8.5 Kg / 18.7 lbs

CINE POWER BATTERY BALLASTS

Extremely efficient, compact, and light-weight DC battery operated ballasts. Capable of powering any discharge lighting lamphead on the market.

DC ballasts deliver greater reliability and double the runtime over conventional inverter based portable lighting systems.

All ballasts incorporate advanced power design for maximised lamp life and true regulation for constant light output. Flicker-free crystal control delivers stable colour temperature and dimming function from 60% to 100% output.

Please enquire about our other types of discharge lighting ballasts: Special high speed output for high speed filming, multi-output ballast array and AC ballasts.



125/200w
Compact DC Ballast




125/200w
Compact DC Ballast



200/400w
Compact DC Ballast



400/800w
Compact DC Ballast



Cine Power Click-Lock

A unique positive lock-on system for Ballasts and other equipment. Machined from solid metal to ensure a durable long-lasting, and easy to use locking system.



Powerport

A unique, compact docking system to run a 125/200W DC ballast from two standard 12-14V lock-on batteries. Integrated over-discharge protection and fuses protect the batteries.

CINE POWER BATTERIES AND BALLASTS



CINE POWER
INTERNATIONAL LTD
www.cinepower.com

CINE POWER INTERNATIONAL LTD
UNITED KINGDOM

tel: +44 (0) 1626 888433 fax: +44 (0) 1626 888435 www.cinepower.com

CINE POWER BATTERIES ARE UNIQUE



There is no comparable battery with the range of features suitable for the Broadcast, Film and Video professional. Do not risk your reputation using anything else, you can rely on the dependable performance of a Cine Power battery.

Safety features are fitted as standard into every battery; internal self-resetting electronic fuses, thermal protection and automatic over-discharge protection. Optional extras include advanced metering and level of charge indication.

Constructed using non-hazardous, high capacity NiMH - Nickel Metal Hydride batteries. They are suitable for all forms of transport without restriction.



CINE POWER BATTERY COMPARISONS	CINE POWER NIMH	LITHIUM LI-ION	LEAD ACID
High capacity batteries safe for transport without restrictions	YES	NO	NO
Long storage life without deterioration and permanent capacity loss	YES	NO	NO
Fast Charge	YES	LIMITED	NO
Low internal resistance	YES	NO	NO
Near-constant discharge voltage	YES	NO	NO
Safe. Tolerant of rough handling and abuse	YES	NO	NO
Low environmental impact, easily and cheaply recyclable	YES	NO	YES
Long term, heavy duty reliable performance	YES	NO	NO

CINE POWER BATTERY CHARGERS

Chargers are an integral part of the Cine Power battery system designed to rapid charge NiMH or NiCd batteries. The dependability of Cine Power batteries is based on their rugged construction and the unique charger technology pioneered by Elemér Nyiry. Proprietary intelligent microprocessor control and multi-stage charging extends battery service life. There is no need to re-cell batteries on a regular basis.

- Operate World-wide 110V / 60Hz or 230V / 50Hz
- No need to discharge battery before charging
- Fully automatic. Advanced microprocessor detects state of battery and charges at appropriate rate.
- Battery can be left connected to charger on standby indefinitely without fear of over-charging
- Multi-stage charging and enhanced diagnostic function extends battery service life
- Rugged and durable construction to resist rough handling and ensure long life



Super Silver Charger

Charger for standard capacity batteries
 Length 210mm/ 8.3"
 Width 125mm/ 5"
 Height 93mm/ 3.7"
 Weight..... 2.6 Kg / 5.8 lb



Mega Charger

Charger for high capacity batteries
 Length 280mm/ 11.1"
 Width 125mm/ 5"
 Height 93mm/ 3.7"
 Weight..... 3.8 Kg / 8.4 lb



Smart Cable

Smart Cable is a self contained meter unit. It incorporates two LCD meters for simultaneous display of voltage and current consumption.



Battery Capacity Tester

Dual channel, free-standing, it will safely simultaneously discharge up to two batteries at a time. It is powered from the battery under test, making it fully portable. Relay outputs are provided for external control of auxiliary equipment.



Dolly Driver

A compact, portable power unit designed to charge any dolly accumulator pump. It gives you total freedom from electrical supply cables whilst retaining total dolly functionality.




Power-Source

AC powered Battery eliminators featuring the same output voltage configurations as our batteries. Fitted with a digital LCD voltmeter and ammeter for continuous output monitoring. Available in a range of configurations to suit your needs.

CAMERA BATTERIES

Powerful batteries for all makes of cameras and associated equipment, including ARRI, SONY, Red, Phantom and Panavision.



BATTERY	HD-60	MAGNUM	HD-40	HD-30	CAMERA POWER	HD POWER BELT
METERS	Voltage and Current	Voltage and Current	Voltage and Current	Voltage and Current	Not available	Not available
AMP HOUR	60Ah	60Ah	40Ah	30Ah	2 x 15Ah	30Ah
WATT HOUR	864Wh	864Wh	576Wh	432Wh	432Wh	432Wh
100W LOAD RUNTIME	8Hrs	8Hrs	5Hrs	4Hrs	4Hrs	4Hrs
CHARGER	Mega	Mega	Mega	Super Silver	Super Silver	Super Silver
OUTPUT SOCKETS	1 x 14V XLR 1 x 14V + 24V LEMO	1 x 14V XLR 1 x 14V + 24V LEMO	1 x 14V XLR 1 x 14V + 24V LEMO	XLR 2 x 14V	XLR 2 x 13.2V	XLR 2 x 14V
NOTE: LEMO SOCKET FOR SONY	switchable to: 1 x 14V XLR 1 x 14V + 28V XLR 1 x 14V + 24V LEMO	switchable to: 1 x 14V XLR 1 x 14V + 28V XLR 1 x 14V + 24V LEMO	switchable to: 1 x 14V XLR 1 x 14V + 28V XLR 1 x 14V + 24V LEMO	switchable to: 1 x 14V + 28V and 2 x 14V	switchable to: 1x 13.2V and 1x 26.4V	switchable to: 2 x 14V and 1 x 14V + 28V
SIZE	H 365mm/ 14.3" L 260mm/ 10.3" W 173mm/ 6.9"	H 214mm / 8.4" L 254mm / 10" W 205mm / 8"	H 287mm/ 11.2" L 226mm / 8.9" W 143mm / 5.7"	H 152mm/ 6" L 240mm/ 9.5" W 152mm/ 6"	H 250mm/ 9.8" L 245mm/ 9.6" W 120mm/ 4.7"	H 127mm/ 5" L 740mm/ 29" W 50mm/ 2"
WEIGHT	17.5Kg / 38.5 lbs	18Kg / 39.6 lbs	12.4Kg / 27.3 lbs	8.5 Kg / 18 lbs	7 Kg / 15.4 lbs	8KG / 17.6 lbs
CABLES	<p>The over-discharge protection device will cut all power to the outputs once the battery has been discharged to the minimum safe level. LED's given warning of cut off and fully discharged state. Over-discharge protection is totally automatic in operation, and will reset itself during subsequent recharge. Recharge time is proportional to the depth of discharge and temperature - typically no more than 5 hours from discharged.</p> <p>Battery casings are machined from a tough, high-impact composite for rugged durability. Belts are low profile quality leather. Advanced battery design ensures maximum power output for the most demanding of loads. Gold plated low loss XLR and Fischer connectors fitted as standard. Batteries can be supplied configured to meet your needs and with almost any connector configured to match your application.</p> <p>Choice of colour Main colour : Grey or Black. Trim colour - Red, Blue, Yellow, White, Grey or Black Faceplates : Anodised to match trim - Red, Back, Blue Logo : Your name or Company logo may be added if artwork is supplied at time of ordering</p>					
	Cables made for any application					